



## Linde E16-01 386

(ET1449 )

<b>Brand</b>	Linde
<b>Model</b>	E16-01 386
<b>Capacity (kg)</b>	1600
<b>Load centre distance (mm)</b>	500
<b>Lift height (mm)</b>	4625
<b>Height (mm)</b>	2121
<b>Masttype</b>	Triplex
<b>Free lift (mm)</b>	1550
<b>Fork length (mm)</b>	1200
<b>Fork carriage width (mm)</b>	980
<b>Length to fork face (mm)</b>	1900
<b>Width (mm)</b>	1050
<b>Drive wheels (size)</b>	18x7x8
<b>Type of tyres, drive wheels</b>	Superelastic
<b>Steering wheels (size)</b>	15x4,5-8
<b>Type of tyres, steering wheels</b>	Superelastic
<b>Energy</b>	AC 3-phase
<b>Engine type</b>	2x5KW+11KW
<b>Transmission</b>	Linde digital control
<b>Operation</b>	Joystick, 2-pedal
<b>Driver's place</b>	Open cabin
<b>Battery</b>	48v 625ah
<b>Lights</b>	Work lights
<b>Equipment</b>	Fork positioner with sideshift, 3. + 4. valve complete ,
<b>Cabin equipment</b>	Panorama spejl
<b>Dead weight (kg)</b>	3285
<b>Approved</b>	This machine is delivered with new statutory safety approval