



## Linde E25-01

(ET1567 )

|                                       |  |
|---------------------------------------|--|
| <b>Brand</b>                          | Linde  |
| <b>Model</b>                          | E25-01   |
| <b>Capacity (kg)</b>                  | 2500   |
| <b>Load centre distance (mm)</b>      | 500  |
| <b>Lift height (mm)</b>               | 5200   |
| <b>Height (mm)</b>                    | 2330   |
| <b>Masttype</b>                       | Triplex  |
| <b>Free lift (mm)</b>                 | 1700   |
| <b>Fork length (mm)</b>               | 1200   |
| <b>Fork carriage width (mm)</b>       | 960  |
| <b>Length to fork face (mm)</b>       | 2300   |
| <b>Width (mm)</b>                     | 1200   |
| <b>Drive wheels (size)</b>            | 23x9x10  |
| <b>Type of tyres, drive wheels</b>    | Superelastic   |
| <b>Steering wheels (size)</b>         | 200/50x10  |
| <b>Type of tyres, steering wheels</b> | Superelastic   |
| <b>Energy</b>                         | AC 3-phase   |
| <b>Engine type</b>                    | 2x9kW+22kW   |
| <b>Transmission</b>                   | Linde digital control  |
| <b>Driver's place</b>                 | Closed cabin   |
| <b>Battery</b>                        | 80V/ 500ah   |
| <b>Lights</b>                         | Road lights, flashing beacon                                 |
| <b>Equipment</b>                      | Forkpositioner/sideshift, full freelif                       |
| <b>Cabin equipment</b>                | Varme, visker, skyderuder i døre                             |
| <b>Dead weight (kg)</b>               | 3700+bat   |
| <b>Approved</b>                       | This machine is delivered with new statutory safety approval |