



## Linde E25-01

(ET1567 )

<b>Brand</b>	Linde
<b>Model</b>	E25-01
<b>Capacity (kg)</b>	2500
<b>Load centre distance (mm)</b>	500
<b>Lift height (mm)</b>	5200
<b>Height (mm)</b>	2330
<b>Masttype</b>	Triplex
<b>Free lift (mm)</b>	1700
<b>Fork length (mm)</b>	1200
<b>Fork carriage width (mm)</b>	960
<b>Length to fork face (mm)</b>	2300
<b>Width (mm)</b>	1200
<b>Drive wheels (size)</b>	23x9x10
<b>Type of tyres, drive wheels</b>	Superelastic
<b>Steering wheels (size)</b>	200/50x10
<b>Type of tyres, steering wheels</b>	Superelastic
<b>Energy</b>	AC 3-phase
<b>Engine type</b>	2x9kW+22kW
<b>Transmission</b>	Linde digital control
<b>Driver's place</b>	Closed cabin
<b>Battery</b>	80V/ 500ah
<b>Lights</b>	Road lights, flashing beacon
<b>Equipment</b>	Forkpositioner/sideshift, full freelif
<b>Cabin equipment</b>	Varme, visker, skyderuder i døre
<b>Dead weight (kg)</b>	3700+bat
<b>Approved</b>	This machine is delivered with new statutory safety approval