



## EP CPYD25-XH3F

(GT1325)

<b>Brand</b>	EP
<b>Model</b>	CPYD25-XH3F
<b>Capacity (kg)</b>	2500
<b>Load centre distance (mm)</b>	500
<b>Lift height (mm)</b>	4300
<b>Height (mm)</b>	2125
<b>Masttype</b>	Triplex
<b>Free lift (mm)</b>	1400
<b>Fork length (mm)</b>	1200
<b>Fork carriage width (mm)</b>	1030
<b>Length to fork face (mm)</b>	2700
<b>Width (mm)</b>	1180
<b>Width - twin wheels (mm)</b>	1600
<b>Drive wheels (size)</b>	700x12
<b>Drive wheels - twin wheels</b>	4 stk. 700x12
<b>Type of tyres, drive wheels</b>	Pneumatic
<b>Steering wheels (size)</b>	600x9
<b>Type of tyres, steering wheels</b>	Pneumatic
<b>Energy</b>	LPG
<b>Engine type</b>	Mitsubishi GK25VL01H, stage 5
<b>Transmission</b>	Torque converter
<b>Driver's place</b>	Open cabin
<b>Lights</b>	Road lights, LED
<b>Equipment</b>	Sideskif, initialift
<b>Cabin equipment</b>	Roof, comfort driver's seat with armrests
<b>Dead weight (kg)</b>	4095