



Linde E16L-01

(ET1658)

| | |
|---------------------------------------|--|
| Brand | Linde |
| Model | E16L-01 |
| Capacity (kg) | 1600 |
| Load centre distance (mm) | 500 |
| Lift height (mm) | 2790 |
| Height (mm) | 1970 |
| Masttype | Duplex |
| Free lift (mm) | 1500 |
| Fork length (mm) | 1200 |
| Fork carriage width (mm) | 980 |
| Length to fork face (mm) | 2062 |
| Width (mm) | 1090 |
| Drive wheels (size) | 18x7x8 |
| Type of tyres, drive wheels | Superelastic |
| Steering wheels (size) | 15x4,5x8 |
| Type of tyres, steering wheels | Superelastic |
| Energy | AC 3-phase |
| Engine type | 2 x 4,6kw + 10kw |
| Transmission | Linde digital control |
| Operation | 2 pedalsystem, joystik i kryds |
| Driver's place | Open cabin |
| Battery | 48v 775ah med central vandpåfyldning |
| Lights | Work lights |
| Equipment | forkposition/sideshift |
| Cabin equipment | Front-, tag- og bagrude |
| Dead weight (kg) | 2005kg+bat |
| Approved | This machine is delivered with new statutory safety approval |