



## Combilift - C8000SL

(DT1347 )

|  |   |
|--|---|
| <b>Brand</b>                           | Combilift   |
| <b>Model</b>                           | C8000SL   |
| <b>Type</b>                            | Four-way sideloader   |
| <b>Capacity (kg)</b>                   | 8000  |
| <b>Load centre distance (mm)</b>       | 600   |
| <b>Lift height (mm)</b>                | 4530  |
| <b>Height (mm)</b>                     | 3280  |
| <b>Masttype</b>                        | Duplex  |
| <b>Free lift (mm)</b>                  | 2220  |
| <b>Width (mm)</b>                      | 2450  |
| <b>Fork length (mm)</b>                | 1150  |
| <b>Fork carriage width (mm)</b>        | 1550  |
| <b>Length to fork face (mm)</b>        | 4100  |
| <b>Drive wheels (size)</b>             | 33x13 3/4x22  |
| <b>Type of tyres, drive wheels</b>     | Superelastic  |
| <b>Steering wheels (size)</b>          | 27x10-12  |
| <b>Type of tyres, steering wheels</b>  | Superelastic  |
| <b>Energy</b>                          | Diesel  |
| <b>Engine type</b>                     | Deutz TCD 3.6L Stage IIIB 75Kw  |
| <b>Transmission</b>                    | Hydrostatic   |
| <b>Driver's place</b>                  | Closed cabin  |
| <b>Lights</b>                          | Lys til kørsel på vej, ekstra LED arbejdslys foran                      |
| <b>Equipment</b>                       | Teleskopudskud med gaffelflytter fra 420-1530 mm, kamera foran og bagpå |
| <b>Opening range - attachment (mm)</b> | 420-1530  |
| <b>Aggregat kapacitet (kg)</b>         | 5000  |
| <b>Cabin equipment</b>                 | Heating, joystick   |
| <b>Dead weight (kg)</b>                | 10500   |
| <b>Approved</b>                        | This machine is delivered with new statutory safety approval            |

