



## Linde E16P-02

(ET1727)

|                                       |  |
|---------------------------------------|--|
| <b>Brand</b>                          | Linde  |
| <b>Model</b>                          | E16P-02  |
| <b>Capacity (kg)</b>                  | 1600   |
| <b>Load centre distance (mm)</b>      | 500  |
| <b>Lift height (mm)</b>               | 5700   |
| <b>Height (mm)</b>                    | 2490   |
| <b>Masttype</b>                       | Triplex  |
| <b>Fork length (mm)</b>               | 1200   |
| <b>Length to fork face (mm)</b>       | 2029   |
| <b>Width (mm)</b>                     | 1040   |
| <b>Drive wheels (size)</b>            | 180/70-8   |
| <b>Type of tyres, drive wheels</b>    | Non-marking superelastic                                     |
| <b>Steering wheels (size)</b>         | 150/75-8   |
| <b>Type of tyres, steering wheels</b> | Non-marking superelastic                                     |
| <b>Energy</b>                         | AC 3-phase   |
| <b>Engine type</b>                    | 2x5KW+11KW   |
| <b>Transmission</b>                   | Linde digital control  |
| <b>Driver's place</b>                 | Open cabin   |
| <b>Battery</b>                        | 48V/625ah  |
| <b>Lights</b>                         | Work lights, flashing beacon                                 |
| <b>Equipment</b>                      | 4 valves   |
| <b>Cabin equipment</b>                | Spejl, skriveplade m/lys                                     |
| <b>Dead weight (kg)</b>               | 3624   |
| <b>Approved</b>                       | This machine is delivered with new statutory safety approval |