



## Linde E12/386-02

(ET1773 )

|                                       |  |
|---------------------------------------|--|
| <b>Brand</b>                          | Linde  |
| <b>Model</b>                          | E12/386-02   |
| <b>Capacity (kg)</b>                  | 1200   |
| <b>Load centre distance (mm)</b>      | 500  |
| <b>Lift height (mm)</b>               | 4625   |
| <b>Height (mm)</b>                    | 2122   |
| <b>Masttype</b>                       | Triplex frisigt m/fuld friløft                               |
| <b>Fork length (mm)</b>               | 1200   |
| <b>Fork carriage width (mm)</b>       | 1050   |
| <b>Length to fork face (mm)</b>       | 1701   |
| <b>Width (mm)</b>                     | 1090   |
| <b>Drive wheels (size)</b>            | 18x7-8   |
| <b>Type of tyres, drive wheels</b>    | Superelastic   |
| <b>Steering wheels (size)</b>         | 15x4,5-8   |
| <b>Type of tyres, steering wheels</b> | Superelastic   |
| <b>Energy</b>                         | AC 3-phase   |
| <b>Engine type</b>                    | 2x3,5 kW   |
| <b>Transmission</b>                   | LDC transistorstyring, 2-pedalsystem                         |
| <b>Operation</b>                      | Joystick i armlæn  |
| <b>Driver's place</b>                 | Open cabin   |
| <b>Battery</b>                        | 24V/625ah  |
| <b>Lights</b>                         | Lys til kørsel på vej, ekstra arbejdslys, BlueSpot           |
| <b>Equipment</b>                      | Integreret forkpotition/sideshift                            |
| <b>Cabin equipment</b>                | Frontrude m/visker, tagrude                                  |
| <b>Dead weight (kg)</b>               | 2695   |
| <b>Approved</b>                       | This machine is delivered with new statutory safety approval |