



## Linde E15-02 (386)

(ET1783 )

<b>Brand</b>	Linde
<b>Model</b>	E15-02 (386)
<b>Capacity (kg)</b>	1500
<b>Load centre distance (mm)</b>	500
<b>Lift height (mm)</b>	4620
<b>Height (mm)</b>	2140
<b>Masttype</b>	Triplex fuld friløft
<b>Free lift (mm)</b>	1519
<b>Fork length (mm)</b>	1200
<b>Length to fork face (mm)</b>	1846
<b>Width (mm)</b>	1050
<b>Drive wheels (size)</b>	18x7-8
<b>Type of tyres, drive wheels</b>	Superelastic
<b>Steering wheels (size)</b>	15x4,5-8
<b>Type of tyres, steering wheels</b>	Superelastic
<b>Energy</b>	AC 3-phase
<b>Engine type</b>	2x3,5 kW
<b>Transmission</b>	Linde digital control
<b>Operation</b>	Fingertip
<b>Driver's place</b>	Open cabin
<b>Battery</b>	24V/1000ah
<b>Charger</b>	24v standard oplader
<b>Lights</b>	Work lights
<b>Equipment</b>	4 ventiler, gaffelflytter/sideskift
<b>Cabin equipment</b>	Indvendig spejl
<b>Dead weight (kg)</b>	3140
<b>Approved</b>	This machine is delivered with new statutory safety approval