



## Linde E25-01 387

(ET1791)

<b>Brand</b>	Linde
<b>Model</b>	E25-01 387
<b>Capacity (kg)</b>	2500
<b>Load centre distance (mm)</b>	500
<b>Lift height (mm)</b>	4560
<b>Height (mm)</b>	2850
<b>Masttype</b>	Duplex
<b>Fork length (mm)</b>	1200
<b>Length to fork face (mm)</b>	2300
<b>Width (mm)</b>	1150
<b>Drive wheels (size)</b>	225/75-10
<b>Type of tyres, drive wheels</b>	Superelastic
<b>Steering wheels (size)</b>	200/50-10
<b>Type of tyres, steering wheels</b>	Superelastic
<b>Energy</b>	AC 3-phase
<b>Engine type</b>	2x9,0 kW
<b>Transmission</b>	Linde digital control
<b>Operation</b>	2 pedal system
<b>Driver's place</b>	Open cabin
<b>Battery</b>	80V
<b>Lights</b>	LED arbejdslys, BlueSpot
<b>Equipment</b>	4 valves
<b>Cabin equipment</b>	Panorama spejl, visker/vasker
<b>Dead weight (kg)</b>	4770
<b>Approved</b>	This machine is delivered with new statutory safety approval