

## EP CPD18TVL (48) Li-Ion

(ET0418(48))

**DKK 0,00**

Excl. VAT and delivery costs

|                                       |   |
|---------------------------------------|---|
| <b>Brand</b>                          | EP  |
| <b>Model</b>                          | CPD18TVL (48) Li-Ion  |
| <b>Type</b>                           | Electric 3-wheel forklift   |
| <b>Capacity (kg)</b>                  | 1800  |
| <b>Load centre distance (mm)</b>      | 500   |
| <b>Lift height (mm)</b>               | 4800  |
| <b>Height (mm)</b>                    | 2240  |
| <b>Masttype</b>                       | Triplex frisigt m/fuld friløft  |
| <b>Free lift (mm)</b>                 | 1530  |
| <b>Length to fork face (mm)</b>       | 1913  |
| <b>Fork length (mm)</b>               | 1200  |
| <b>Fork carriage width (mm)</b>       | 1040  |
| <b>Width (mm)</b>                     | 1070  |
| <b>Gangbreddebehov / AST (mm)</b>     | 3400  |
| <b>Venderadius (mm)</b>               | 1550  |
| <b>Drive wheels (size)</b>            | 18x7-8  |
| <b>Type of tyres, drive wheels</b>    | Non-marking superelastic  |
| <b>Steering wheels (size)</b>         | 15x4,5-8  |
| <b>Type of tyres, steering wheels</b> | Non-marking superelastic  |
| <b>Energy</b>                         | AC 3-phase  |
| <b>Engine type</b>                    | 2x5kW + 11kW  |
| <b>Battery</b>                        | 80V/205Ah Li-Ion  |
| <b>Charger</b>                        | Integreret oplader - nem opladning via ladestik i siden                 |
| <b>Transmission</b>                   | Tranistor control   |
| <b>Operation</b>                      | Mekanisk betjening af hydraulikventiler                                 |
| <b>Equipment</b>                      | Friløft, 4 ventiler, Cascade gaffelflytter/sideskift                    |
| <b>Driver's place</b>                 | Open cabin  |
| <b>Cabin equipment</b>                | Kop- og dokumentholder, aflæggerrum, indstillelig rat, multidisplay LCD |

